


# CP-X308 series

## Key Features

- 2,600 ANSI Lumens
- Native XGA Resolution
- 8.8 lbs.
- 2 RGB Inputs / 1 RGB Output
- 802.11 b/g Connect & Present with 4 PCs wirelessly
- 7 Watt Audio Output
- 29 dB (Whisper Mode)
- Remote Control with My Buttons
- Component / Composite / S-Video Inputs
- My Screen / My Memory
- Network Control, Maintenance, & Security
- Approx. 3,000 hrs. (Whisper Mode)
- Kensington Slot and Security Bar
- Side-Mounted High Performance Filter



## Specifications [Preliminary]

Model Name	CP-X308 Series	
Liquid Crystal Panel Structure	0.63" Polysilicon Active-matrix TFT x 3	
Number of Pixels	786,432 Pixels	
Resolution	Video	540 TV lines
	RGB	1024 dots x 768 lines
Colors	16.7 million colors	
Aspect Ratio	Native 4:3 / 16:9 compatible	
Lens	F1.7 - 1.9	
Throw Ratio (distance : width)	1.5 - 1.8 : 1	
Lamp	220W UHB	
Brightness	2,600 ANSI Lumens	
Expected lamp Life	Approximately 2,000 hours (normal) 3,000 hours (whisper)	
Contrast Ratio	500 : 1	
Speaker Output	7W (1 speaker)	
Power Supply	AC100 - 120V / AC220 - 240V 50/60 Hz Power	
Power Consumption	320W	
Operating Temperature	5°C - 35°C (41°F - 95°F)	
Input Signals	RGB	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC13" MAC16"
	Composite Video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N
	Component Video	480i, 576i, 480p, 720p, 1080i
Acoustic Noise Level	35 dB (29 dB in whisper mode)	
H-Sync	15 kHz - 106 kHz	
V-Sync	50 kHz - 120 kHz	
Auto Vertical Keystone	+ / - 30°	
Approvals	UL60950 / C-UL, FCC Part15, Class B, EN60950	
RGB Input	Analog RGB	15-pin D-sub connector x 2
RGB Output	RGB	15-pin D-sub connector x 1
Video Input	S-Video	Mini DIN 4-pin connector x 1
	Composite Video	RCA jack x 1
	Component Video	RCA jack x 3
Audio	Input	Stereo mini jack x 2, RCA (L/R) x 1 pair
	Output	Stereo mini jack x 1
Other		SD Card, USB 2.0 Memory
Wireless		802.11 b/g
Ethernet		RJ-45 port / 100 base-T
Control Terminals		9-pin D-sub connector x 1 (RS-232 control)
Other		USB connector (USB mouse) x 1
Dimensions (W x H x D)	13.4" x 10.6" x 4.6"	
Weight	8.8 lbs.	
Additional Features	Digital Gamma Correction, Whiteboard/Blackboard Mode, Input Source Naming	
Supplied Accessories	Remote Control, Batteries (AA), RGB cable, US power cord, Multiple language operator / Safety Manual, Soft Case, SD Wireless Card	
Lamp	CPX400/300/200LAMP (DT00841)	
Remote Control	HL02227	
Filter	MU04951	

### Screen Size 4:3      Throw Distance

Diagonal*	Width*	Min*	Max*
30	24	35	43
60	48	71	86
80	64	95	115
100	80	119	143
120	96	143	172
150	120	179	216
200	160	240	288
300	240	360	432

Throw Ratio: 1.5 - 1.8:1 (distance : width)  
\*Measured in inches

